

This material does not require any special care; surfaces are very easy to clean. This applies to smooth, matt, and textured finishes.

### **Light Soiling (Fresh)**

The surface can be cleaned with paper towels, clean soft textile cloths (dry or damp), or a soft sponge. Streaks most often occur when the surface is cleaned with organic solvents in combination with cold water and also when repeatedly using the same cloths or window cleaning chamois. For perfect, streak-free cleaning, it is recommended to wipe the surface with warm water and then dry it using commonly available paper or microfiber cloths.

### **Heavier Soiling**

Cleaning with hot water, a clean seamless cloth, a microfiber cloth, sponge, or soft brush is recommended. Common household cleaning agents or liquid soap (both without abrasive components) can be used. Then wipe the surface with a damp cloth to remove all cleaning agent residues to prevent streaks. Dry the doors with an absorbent textile or paper towel.

### **Cleaning Agents That Must Not Be Used Under Any Circumstances**

- Abrasive and scouring agents (abrasive powders, sponges with a rough side, steel wool)
- Polishing agents, furniture cleaners, bleaching agents
- Cleaning agents with strong acids and strong acid salts
- Steam cleaning devices

### **Maintenance Instructions for Matt Surfaces (e.g., SM, ST9 Texture)**

Common dirt can be removed without difficulty. However, it is important to avoid cleaning the surface with sharp cleaning agents/powders, steel wool, polishing agents, detergents, furniture cleaners, and cleaning agents with strong acids. These agents, as well as overly rough cloths or sponges, can cause glossy spots, which means irreversible damage to the matt surfaces. Greasy contamination should be removed as soon as possible (within 48 hours at the latest).

### **Maintenance Instructions for Deep Surfaces (e.g., ST22, Fleetwood ST28 to ST38, etc.)**

These surfaces are more resistant and less prone to mechanical or chemical damage. However, even here, a specific cleaning process must be followed. Clean in the direction of the texture. Otherwise, all other instructions described in the previous paragraphs apply depending on the level of soiling.

**Warning:** Individual parts of T.segment doors are joined together with structural connectors, which involves milling the glued edge of individual parts. This reduces moisture resistance compared to T.komplet products, where resistance to moisture and liquids is very high. Therefore, avoid cleaning with excessively wet cloths and any liquid seepage.